Toppac Solutions For Food Datasheet

Product dimension 95*95 mm

/olume 360 ml



Product Cup 4016

Shape Square

Product Lid - Standard Product no. 3010

		9		1		
		CS PP)		
Weight	15,0 gram	± 2 %			Closure system	Tamper Evident Tab Snap-on Protective collar
Dimension, External	Top Bottom	95,0 mm 73,36 mm				
Packaging (WxLxH)	Unit Scantainer Box	Pcs. 7.296 960	Units per pallet 1 15	Pcs. /pallet 7.296 14.400	Unit size mm 1200 x 800 x 1080 800 x 400 x 450	Pallet height mm 1200 x 800 x 1230 1200 x 800 x 2400
Decoration possible	IML	Toppac sta	ndard colours.			
Safety and performance	The needed strength in the product is different and there are several different factors to consider in each situation. Toppac strongly recommends customers to make their own trials and tests to ensure strength during packing, stacking, shipping and the durability of the product itself.					
Raw material	PP	Polypropyl	ene.			
Raw material Temperature	PP Hot filling	The materi filling. Proc	al chosen has a ve	85-95°C. It is th	ne responsibility of t	ing is suitable for hot he customer to test
		The materi filling. Proc actual proc Random PF	al chosen has a ver duct temperature 8 duct in real temper Presists to 5°C. Blo	35-95°C. It is the ature before a ck PP resists t	ne responsibility of t approval for use. emperature to - 20°	-
	Hot filling	The materi filling. Proc actual proc Random PF of the cust Within the of 0.025%	al chosen has a ver duct temperature & duct in real temper Presists to 5°C. Blo omer to test actua industry, deviation (25 pcs. per 100.00	s5-95°C. It is the ature before a cick PP resists to I product in resists in the product in the	ne responsibility of t approval for use. emperature to - 20° al temperature befo uct specification acc	he customer to test C. It is the responsibility ore approval for use. ording to this datasheet . Within this margin it is
Temperature	Hot filling Cold products	The materi filling. Proc actual proc Random PF of the cust Within the of 0.025% not seen as The compli guaranteed responsible	al chosen has a verification of the product of the	as-95°C. It is the ature before a cick PP resists to a product in resists in the product to the technom date of deladuct. Suitable	ne responsibility of temperature to - 20° al temperature beformation according to the properation accor	c. It is the responsibility ore approval for use. ording to this datasheet . Within this margin it is and Conditions. In this data sheet is od we cannot be held are protection from

Toppac - Metervej 2 - DK-8940 Randers SV

www.toppac.dk

All specifications are subject to revision without notice

Updated revision: 1 December 2021