## Toppac Solutions For Food Datasheet

Product dimension 95\*95 mm

Volume 280 ml



Product Cup 4014

Shape Square

Product Lid - Standard Product no. 3010

|                        |                     | رکی  |                  | )            |   |  |
|------------------------|---------------------|--|------------------|--------------|---|--|
| Weight                 | 12,5 gram           | ± 2 %  |                  |              | Closure system                                  | Tamper Evident Tab                           |
|                        |                     |  |                  |              |   | Snap-on                                      |
|                        |                     |  |                  |              |   | Protective collar                            |
| Dimension, External    | Тор                 | 95,0 mm  |                  |              |   |  |
| ·                      | Bottom              | 76,1 mm  |                  |              |   |  |
| Packaging (W x L x H)  | Unit                | Pcs.   | Units per pallet | Pcs. /pallet | Unit size mm                                    | Pallet height mm                             |
|                        | Scantainer          | 7.584  | 1                | 7.584        | 1200 x 800 x 1080                               | 1200 x 800 x 1230                            |
|                        | Box                 | 992  | 15               | 14.880       | 800 x 400 x 450                                 | 1200 x 800 x 2400                            |
| Decoration possible    | IML                 | Toppac sta   | indard colours.  |              |   |  |
| Safety and performance | situation. Toppac s | trongly recom  |                  | make their o | ral different factors to wn trials and tests to | o consider in each<br>ensure strength during |
| Raw material           | PP                  | Polypropyl   | ene.             |              |   |  |
| Temperature            | Hot filling         | The material chosen has a very good resistance and the packaging is suitable for hot |                  |              |   |  |

| Raw material | PP            | Polypropylene.  |  |
|--------------|---------------|---|--|
|              |               |   |  |
| Temperature  | Hot filling   | The material chosen has a very good resistance and the packaging is suitable for hot filling. Product temperature 85-95°C. It is the responsibility of the customer to test actual product in real temperature before approval for use. |  |
|              | Cold products | Random PP resists to 5°C. Block PP resists temperature to - 20°C. It is the responsibility of the customer to test actual product in real temperature before approval for use.  |  |

| Quality | Deviations | Within the industry, deviations in the product specification according to this datasheet of 0.025% (25 pcs. per 100.000 pcs.) are considered acceptable. Within this margin it is not seen as a defect. We also refer you to our Standard Terms and Conditions.  |
|---------|------------|--|
|         | Shelf life | The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months from date of delivery. After this period we cannot be held responsible for use of the product. Suitable storage conditions are protection from direct sunlight, rain, very low temperatures or very high temperatures over a long period. |
|         | Approvals  | All Toppac products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended for food contact, unless otherwise stated. In accordance to EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.        |

Toppac - Metervei 2 - DK-8940 Randers S\

www.toppac.dk

All specifications are subject to revision without notice