Торрас	Solutions For Food					Datasheet	
Product dimension	95*128 mm	F		Product	Cup	4024	
Volume	280 ml				Shape	Rectangular	
	_			Product	Lid - Standard	Product no. 3020	
		3					
		PP				1	
Weight	13,5 gram	± 2 %			Closure system	Tamper Evident Tab Snap-on Protective collar	
Dimension, External	Тор	127,87 mm					
	Bottom	116,97 mm					
Packaging (W x L x H)	Unit Scantainer	Pcs. 6.142	Units per pallet 1	Pcs. /pallet 6.142	Unit size mm 1200 x 800 x 1080	Pallet height mm 1200 x 800 x 1230	
	Box	792	15	11.880	800 x 400 x 450	1200 x 800 x 1230 1200 x 800 x 2400	
Decoration possible	IML	Toppac standard colours.					
	packing, stacking, sh			roduct itself.			
Raw material	PP	Polypropyle	ne.				
Temperature	Hot filling	The material chosen has a very good resistance and the packaging is suitable for hot filling. Product temperature 85-95°C. It is the responsibility of the customer to test actual product in real temperature before approval for use.					
	Cold products	Random PP resists to 5°C. Block PP resists temperature to - 20°C. It is the responsibility of the customer to test actual product in real temperature before approval for use.					
Quality	Deviations	ions Within the industry, deviations in the product specification according to this datashee 0.025% (25 pcs. per 100.000 pcs.) are considered acceptable. Within this margin it is n seen as a defect. We also refer you to our Standard Terms and Conditions.					
	Shelf life	The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months from date of delivery. After this period we cannot be held responsible for use of the product. Suitable storage conditions are protection from direct sunlight, rain, very low temperatures or very high temperatures over a long period.					
	Approvals All Toppac products comply with the European Union Commission Regula 10/2011/EC with amendments, relating to materials and articles intended contact, unless otherwise stated. In accordance to EU legislation, it is the the customer to ensure that the supplied product is suitable for the inten						

Toppac - Metervej 2 - DK-8940 Randers SV

www.toppac.dk

All specifications are subject to revision without notice